

WorldMax



LUBEPower

POWER HAR BOOND MEIN



**We Don't Just Create Clients,
We Create Long-term Relationships.**

PRODUCT CATALOGUE

LUBEPower PRIVATE LIMITED

CERTIFICATES

आयकर विभाग
INCOME TAX DEPARTMENT



भारत सरकार
GOVT. OF INDIA

ई-स्थायी लेखा संख्या कार्ड
e - Permanent Account Number (e-PAN) Card
AAGCL4665F

नाम / Name	LUBEPOWER PRIVATE LIMITED
निगमन/गठन की तारीख Date of Incorporation / Formation	02/09/2025
	

- ✓ Permanent Account Number (PAN) facilitate Income Tax Department linking of various documents, including payment of taxes, assessment, tax demand tax arrears, matching of information and easy maintenance & retrieval of electronic information etc. relating to a taxpayer. स्थायी लेखा संख्या (पैन) एक कठोरता से संबंधित विभिन्न दस्तावेजों को जोड़ने में आयकर विभाग को सहायक होता है, जिसमें करों के भुगतान, आकलन, कर योग, टैक्स भुगतान, भुगतान के विवरण और इलेक्ट्रॉनिक जानकारी का आदान-प्रदान करने में शामिल आदि भी शामिल हैं।
- ✓ Quoting of PAN is now mandatory for several transactions specified under Income Tax Act, 1961 (Refer Rule 114B of Income Tax Rules, 1962) आयकर अधिनियम, 1961 के तहत निर्दिष्ट कई लेनदेन के लिए स्थायी लेखा संख्या (पैन) का उल्लेख अब अनिवार्य है। (आयकर नियम, 1962 के नियम 114B, का संदर्भ दें)
- ✓ Possessing or using more than one PAN is against the law & may attract penalty of upto Rs. 10,000. एक से अधिक स्थायी लेखा संख्या (पैन) का रखना या उपयोग करना, कानून के विरुद्ध है और इसके लिए 10,000 रुपये तक का दंड लगाया जा सकता है।
- ✓ The PAN Card enclosed contains Enhanced QR Code which is readable by a specific Android Mobile App. Keyword to search this specific Mobile App on Google Play Store is "Enhanced QR Code Reader for PAN Card". संलग्न पैन कार्ड में एक बढ़ावा दिया गया QR कोड शामिल है जो एक विशिष्ट एंड्रॉइड मोबाइल ऐप को खोजने के लिए कीवर्ड "Enhanced QR Code Reader for PAN Card" है।

Cut



Electronically issued and Digitally signed ePAN is a valid mode of issue of Permanent Account Number (PAN) post amendments in clause (c) in the Explanation occurring after sub-section (8) of Section 139A of Income Tax Act, 1961 and sub-rule (8) of Rule 114 of the Income Tax Rules, 1962. For more details, [click here](#)



Government of India
Form GST REG-06
[See Rule 10(1)]
Registration Certificate

Registration Number : 03AAGCL4665F1ZM

1. Legal Name	LUBEPOWER PRIVATE LIMITED		
2. Trade Name, if any	LUBEPOWER PRIVATE LIMITED		
3. Additional trade names, if any			
4. Constitution of Business	Private Limited Company		
5. Address of Principal Place of Business	Building No./Flat No.: SHOWROOM NO 04 Road/Street: CHHAJJU MAJRA ROAD Locality/Sub Locality: MUNDI KHARAR City/Town/Village: Mohali District: SAS Nagar State: Punjab PIN Code: 140308		
6. Date of Liability			
7. Period of Validity	From	17/03/2026	To Not Applicable
8. Type of Registration	Regular		
9. Particulars of Approving			

Signature

Name

Designation

Jurisdictional Office

Date of issue of Certificate

17/03/2026

Note: The registration certificate is required to be prominently displayed at all places of business in the State.

This is a system generated digitally signed Registration Certificate, issued based on electronic approval of application on 17/03/2026.

LUBEPOWER PRIVATE LIMITED

BIKE & MOPED ENGINE OIL

20W40 API SJ/JASO MA



DESCRIPTION

20W40 API SJ/JASO MA is a high performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too.

MEETS OR EXCEEDS
API SJ/JASO MA

SPECIFICATION

Appearance	VISUAL	CSB
Density @29.5 °C.gm/CC	ASTM D 4052	0.852
Viscosity @100°C, cSt	ASTM D 445	14.16
Viscosity @40°C, cSt	ASTM D 445	110.90
Viscosity Index	ASTM D 2270	120
Pour Point, °C	ASTM D 97	-22
Flash Point, °C	ASTM D 92	231
TBN, mgKOH/gm	ASTM D 892	5.6

PACKAGING SIZE

900ml, 1Ltr, 1200ml, 20ltr, 55ltr, 210ltr

20W40 API SL/JASO MA2

DESCRIPTION

20W40 API SL/JASO MA2 is a high performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too.

MEETS OR EXCEEDS
API SL/JASO MA2

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.865
Viscosity @100°C, cSt	ASTM D 445	14.27
Viscosity @40°C, cSt	ASTM D 445	114.88
Viscosity Index	ASTM D 2270	125
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	235
TBN, mgKOH/gm	ASTM D 892	6.3

PACKAGING SIZE

900ml, 1Ltr, 1200ml, 20ltr, 55ltr, 210ltr



20W40 API SM/JASO MA2

DESCRIPTION

20W40 API SM/JASO MA2 is a high performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too.

MEETS OR EXCEEDS
API SM/JASO MA2

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.869
Viscosity @100°C, cSt	ASTM D 445	15.38
Viscosity @40°C, cSt	ASTM D 445	127.48
Viscosity Index	ASTM D 2270	125
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	237
TBN, mgKOH/gm	ASTM D 892	6.5

PACKAGING SIZE

900ml, 1Ltr, 1200ml, 20ltr, 55ltr, 210ltr



20W40 API SN/JASO MA 2

DESCRIPTION

20W40 API SN/JASO MA2 is a high performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too.

MEETS OR EXCEEDS
API SN/JASO MA2

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.875
Viscosity @100°C, cSt	ASTM D 445	16.50
Viscosity @40°C, cSt	ASTM D 445	140.08
Viscosity Index	ASTM D 2270	126
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	241
TBN, mgKOH/gm	ASTM D 892	6.7

PACKAGING SIZE

900ml, 1Ltr, 1200ml, 20ltr, 55ltr, 210ltr



BIKE & MOPED ENGINE OIL

10W30 API SN/JASO MB



DESCRIPTION

10W-30 API SN/JASO MB is an synthetic bike engine oil enhanced with high quality additives for the latest generation four stroke motorcycles. This high quality oil helps maintain a cleaner engine and improves efficiency.

MEETS OR EXCEEDS
API SN/JASO MB

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.851
Viscosity @100°C, cSt	ASTM D 445	10.69
Viscosity @40°C, cSt	ASTM D 445	66.81
Viscosity Index	ASTM D 2270	149
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	238
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

600ml, 650ml, 800ml, 850ml 900ml, 1Ltr, 1200ml, 20ltr, 55ltr, 210ltr

10W40 API SN/JASO MB

DESCRIPTION

10W-40 API SN/JASO MB is an synthetic bike engine oil enhanced with high quality additives for the latest generation four stroke motorcycles. This high-quality oil helps maintain a cleaner engine and improves efficiency.

MEETS OR EXCEEDS
API SN/JASO MB

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.860
Viscosity @100°C, cSt	ASTM D 445	15.50
Viscosity @40°C, cSt	ASTM D 445	105.95
Viscosity Index	ASTM D 2270	155
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	232
TBN, mgKOH/gm	ASTM D 892	7.8

PACKAGING SIZE

800ml, 900ml, 1Ltr, 1200ml, 20ltr, 55ltr, 210ltr



15W50 API SN/JASO MA2

DESCRIPTION

15W-50 API SN/JASO MA2 is a synthetic blend formulated specifically for new generation higher CC four- stroke motorcycles ideal for daily commute or recreational riding.

MEETS OR EXCEEDS
API SN / JASO MA2

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.860
Viscosity @100°C, cSt	ASTM D 445	18.90
Viscosity @40°C, cSt	ASTM D 445	155.10
Viscosity Index	ASTM D 2270	138
Pour Point, °C	ASTM D 97	-28
Flash Point, °C	ASTM D 92	244
TBN, mgKOH/gm	ASTM D 892	6.2

PACKAGING SIZE

1.7ltr, 2.5ltr, 3ltr, 20ltr, 55ltr, 210ltr



CAR & LMV ENGINE OIL

10W40 API SN/CF



DESCRIPTION

Fully Synthetic Engine Oil API SN/CF SAE 10W40 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance.

MEETS OR EXCEEDS
API SN/CF

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.860
Viscosity @100°C, cSt	ASTM D 445	15.50
Viscosity @40°C, cSt	ASTM D 445	105.95
Viscosity Index	ASTM D 2270	155
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	232
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1 Ltr, 3 Ltr, 3.5 Ltr, 4 Ltr, 5Ltr, 6 Ltr
7.5 Ltr, 20 Ltr, 55 Ltr, 210 Ltr

5W30 API SP

DESCRIPTION

Fully Synthetic Engine Oil API SP SAE 5W30 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance.

MEETS OR EXCEEDS
API SP ILSAC GF-6A

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.835
Viscosity @100°C, cSt	ASTM D 445	11.5
Viscosity @40°C, cSt	ASTM D 445	68.20
Viscosity Index	ASTM D 2270	164
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1 Ltr, 3 Ltr, 3.5 Ltr, 4 Ltr, 5Ltr, 6 Ltr 7.5 Ltr,
20 Ltr, 55 Ltr, 210 Ltr



5W40 API SP

DESCRIPTION

Fully Synthetic Engine Oil API SP SAE 5W40 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance.

MEETS OR EXCEEDS
API SP ILSAC GF-6A

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.835
Viscosity @100°C, cSt	ASTM D 445	15.20
Viscosity @40°C, cSt	ASTM D 445	95.65
Viscosity Index	ASTM D 2270	168
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1 Ltr, 3 Ltr, 3.5 Ltr, 4 Ltr, 5Ltr, 6 Ltr 7.5 Ltr,
20 Ltr, 55 Ltr, 210 Ltr



15W30 API SN/CF

DESCRIPTION

Fully Synthetic Engine Oil API SN/CF SAE 15W30 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance.

MEETS OR EXCEEDS
API SN/CF ACEA A5/B5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C.gm/CC	ASTM D 4052	0.835
Viscosity @100°C, cSt	ASTM D 445	11.50
Viscosity @40°C, cSt	ASTM D 445	68.20
Viscosity Index	ASTM D 2270	164
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1 Ltr, 3 Ltr, 3.5 Ltr, 4 Ltr, 5Ltr, 6 Ltr 7.5 Ltr,
20 Ltr, 55 Ltr, 210 Ltr



PERFORMANCE THAT LASTS, RIDE AFTER RIDE.

For riders seeking lasting protection



**SPECIAL
FORMULATION**



**360° ENGINE
DEFENCE**



**ULTIMATE
PERFORMANCE**



**SMOOTH
RIDE**



OFFICE

SCO 85-86 1ST,
FLOOR SECTOR 17D,
Chandigarh- 160017

PLANT ADDRESS

Plot. No. 5 Dwarkesh Industries
Bardoli Rd Bagumra Surat Bardoli
Rd, Jolva, Kadodara, Gujarat, 394305

CONTACT

customer@lubepower.in
www.lubepower.in
Customer Support:-
+91 99147 08800
Social Media:-  



LUBEPOWER

POWER HAR BOOND MEIN

